



## LFS-40CL Polyester (PET)

FEATURES
<ul style="list-style-type: none"> <li>▪outstanding clarity</li> <li>▪good glue adhesion</li> <li>▪good ink adhesion</li> <li>▪excellent chemical resistance</li> <li>▪supported or unsupported</li> <li>▪good die cutting</li> </ul>

**DESCRIPTION:** LFS-40CL is treated to promote good adhesion.

**APPLICATIONS:** Labeling of household cleaners & detergents

**Available gauges:**

Gauge:	.00048	.00092	.00142	.002	.003	.004	.005	.007
Yield:(in.sq./lb.)	42,000	21,000	14,000	10,000	6,500	5,000	4,000	2,800

<b>PHYSICAL PROPERTIES:</b>			
<u>Property</u>	<u>Units</u>	<u>Testing Method</u>	<u>Typical Value for</u>
Gauge	mil		.00092
Yield	in.sq./lb.		21,000
Shrinkage	%	ASTM D2838	MD 2.5
(30 min @ 150°C)			TD 2.5
Modules	PSI MD	ASTM D 882	550,000
Co Efficient of Friction	Kinetic	ASTM D 1894	0.36
	Static		0.40
Density	g/cm <sup>3</sup>	ASTM D1505	1.395
Haze	%	ASTM D1003	2.0 max.

Comments: All information contained herein represents the best information available to L&K Industries at the time of preparation. We make no guarantee of product performance and all recommendations with respect to its end use, either expressed or implied.