



## WPF-40CL Clear Polyester

### FEATURES

- outstanding clarity
- good glue adhesion
- very strong film
- approved for direct food contact
- excellent chemical resistance

**DESCRIPTION:** WPF-40CL is treated to promote good adhesion.

**APPLICATIONS:** Hardware, Cosmetics, Toys, Glassware, Pharmaceutical

**Available gauges and Yields (in.sq/lb.)**

Gauge:	.00048	.00092	.00142	.002	.003	.004	.005	.007
Yield:	42,000	21,000	14,000	10,000	6,500	5,000	4,000	2,800

### PHYSICAL PROPERTIES:

<u>Property</u>	<u>Units</u>	<u>Testing Method</u>	<u>Typical Value for</u>
Gauge	mil		.00092
Yield	in.sq./lb.		21,000
Shrinkage	%	ASTM D2838	MD 2.5
(30 min @ 150°C)			TD 2.5
Modules	PSI MD	ASTM D 882	550,000
Co Efficient of Friction	Kinetic	ASTM D 1894	0.36
	Static		0.40
Density	g/cm <sup>3</sup>	ASTM D1505	1.395
Haze	%	ASTM D1003	2.0 max.

Comments: All information contained herein represents the best information available to L&K Industries at the time of preparation. We make no guarantee of product performance and all recommendations with respect to its end use, either expressed or implied.